

## Product Data Sheet: B1000

### 2mil Wht PET TC | zillaBite | 50#

Rev. No. 04.01.01 | Date 23AUG24

This is a white, glossy, polyester film with a high performance print receptive topcoat.

high opacity  
great heat resistance  
great chemical resistance  
excellent tear strength  
good dimensional stability

caliper (+/- 10%)	2mil
tensile MD/CD (lbs/in)	21k / 31k
elongation % MD/CD	160 / 90
gloss (60°)	52
opacity 200/700 gauge	90 / 99

facestock

print methods: flexographic, thermal transfer

### aggressive UV acrylic adhesive for extended durability

ZillaBite is a highly versatile adhesive engineered to meet a wide range of application demands. It offers long-lasting durability, making it an excellent choice for outdoor use, where reliability is crucial. As a UV adhesive, zillaBite is solvent-free, providing a safer and more sustainable option without compromising on strength or efficiency.

RT loop tack SS (PLI)	5.2
<u>180° peel 15 min dwell (PLI)</u>	
stainless steel	5.2
HDPE	1.4
<u>180° peel 24 hour dwell (PLI)</u>	
stainless steel	6.1
HDPE	1.6



caliper (+/- 10%)	1.8mil
curing wavelength (nm)	220-300
min app temp (°F)	-25
service range (°F)	-40—375
percent solids	100
appearance after cure	colorless

adhesive



This is a 50# bleached, super calendered kraft liner.  
This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 3.1mil

total caliper (+/- 10%) 6.1mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity  
estimated roll weight may vary substantially: width (in) x length (in) x 0.0324  
published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

liner