

## Product Data Sheet: C1235

### Direct Thermal TC | timberTack | 40#

Rev. No. 04.01.01 | Date 15OCT24

This direct thermal is a topcoated, medium sensitivity face stock designed for use in standard speed printers.

- print speeds up to 8ips
- good chemical & environmental resistance
- high bar code scan rates
- scuff resistant
- 190 sensitivity

caliper (+/- 10%)	3.1mil
brightness (%)	77
MD/CD tensile (lbs/in)	35/17
MD/CD tear strength (g)	45/45

facestock

print methods: direct thermal

### an aggressive rubber adhesive for wood & horticulture

TimberTack's secret weapon is its surprisingly soft formula. This clever extra aggressive adhesive seeps into every pore and crevice, forming an unbreakable bond with even the roughest, most textured materials. Unlike stiff adhesives that bridge over uneven surfaces, timberTack's soft formula allows it to fill the gaps to create a larger bonding surface for ultimate strength. Nature Lover's Rejoice, timberTack's solvent-free formula is an eco-friendly choice for a wide range of horticultural applications.

- extra aggressive
- moderately soft adhesive
- high surface contact
- excellent initial tack
- high flow properties
- great cold resistance
- moderate heat resistance



caliper (+/- 10%)	1.4mil
min app temp (°F)	10
service range (°F)	-60—145
180° peel (PLI)	5
RT loop tack (PLI)	6
SAFT (°F)	160

adhesive



This is a 40# bleached, super calendered kraft liner.  
This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%)	2.4mil
-------------------	--------

liner

total caliper (+/- 10%) 6.9mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity  
published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty