

Product Data Sheet: C1036

50# Coated TT Opaque | crocLock HCW | 40#

Rev. No. 04.01.01 | Date 19DEC24

The 50# Coated TT Opaque is a thermal transfer paper coated for flexographic preprinting and with an opaque black barrier.

- black coated opaque barrier
- smooth surface for good bar code reproduction
- smudge resistance for durable bar code image
- high strength for fast matrix stripping

caliper (+/- 10%)	3.1mil
smoothness (5S, PPS)	2.00
brightness %	85
CD tensile (lbs/in)	17
MD tear (g)	42

print methods: thermal transfer with flexographic preprinting

facestock

an aggressive hot-melt rubber adhesive for packaging

CrocLock's aggressive tack bites ahold of most surfaces, but it really shines with everyday packaging jobs. Plus, its excellent on-press convertibility keeps your production lines humming. When it comes to boxes, bottles, and shrink wrap, crocLock is the dependable choice that gets the job done.

- Quick-Tack Properties: label in a Flash with instant adhesion.
- Dust and Debris Resistance: Conquers dust, dirt, and debris for reliable hold in any environment.

high initial tack
moderate temperature resistance
great adhesion on textured surfaces



caliper (+/- 10%)	1.2mil
min app temp (°F)	30
service range (°F)	-40—145
180° peel (PLI)	5.5
RT loop tack (PLI)	6
SAFT (°F)	140

adhesive



This is a 40# bleached, super calendered kraft liner.
This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 2.4mil

total caliper (+/- 10%) 6.7mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity
published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

liner