

## Product Data Sheet: C1037

### 50# Coated TT | snappLock HCW | 40#

Rev. No. 04.01.01 | Date 19DEC24

The 50# Coated TT is a thermal transfer paper coated for flexographic preprinting.

- smooth surface for good bar code reproduction
- smudge resistance for durable bar code image
- high strength for fast matrix stripping
- high brightness and blue-white shade for good label appearance

caliper (+/- 10%)	3.1mil
smoothness (5S, PPS)	2.00
brightness %	85
CD tensile (lbs/in)	17
MD tear (g)	42
opacity %	87

print methods: thermal transfer

facestock

### an aggressive hot-melt adhesive for cylindrical applications

SnappLock is a high-performance adhesive boasting exceptional versatility. It has a high initial tack & peel, conquering diverse substrates, including cylindrical applications. Experience increased production efficiency thanks to snappLock's superior die-cutting properties, ensuring consistent, clean cuts.

- high performance
- superior tack
- high surface adhesion versatility
- excellent die-cutting
- high temperature resistance



caliper (+/- 10%)	1.2mil
min app temp (°F)	40
service range (°F)	-40—190
180° peel (PLI)	7.2
RT loop tack (PLI)	11.3
SAFT (°F)	160

adhesive



This is a 50# bleached, super calendered kraft liner.  
This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%)	3.1mil
-------------------	--------

total caliper (+/- 10%) 7.4mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity  
published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

liner