

Product Data Sheet: C1038L

1.5mil Clr PET STC | snappLock | 40#

Rev. No. 04.01.01 | Date 19DEC24

This is a 1.5mil Polyester liner. This PET liner is designed to offer excellent die cutting and label dispensing.

caliper (+/- 10%)	1.4mil
CD tensile (k lbs/in)	23

liner

an aggressive hot-melt adhesive for cylindrical applications

SnappLock is a high-performance adhesive boasting exceptional versatility. It has a high initial tack & peel, conquering diverse substrates, including cylindrical applications. Experience increased production efficiency thanks to snappLock's superior die-cutting properties, ensuring consistent, clean cuts.

- high performance
- superior tack
- high surface adhesion versatility
- excellent die-cutting
- high temperature resistance



caliper (+/- 10%)	0.9mil
min app temp (°F)	40
service range (°F)	-40—190
180° peel (PLI)	7.2
RT loop tack (PLI)	11.3
SAFT (°F)	160

adhesive



This is a 40# bleached, super calendered kraft liner.
This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%)	2.4mil
-------------------	--------

total caliper (+/- 10%) 4.7mil

liner

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity
published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty