



Product Data Sheet: C1077

54# Semigloss TE | timberTack | 40#

Rev. No. 04.01.01 | Date 26DEC24



The 54# Semigloss TE is a premium coated semigloss porous paper material that allows excellent ink absorbtion. When removed, the material delaminates to indicate tampering.

 Designed for high end labels 	caliper (+/- 10%)	2.7mil
 sharper resolution allows photos to pop 	opacity %	87
 greater contrast between light and dark shades 	gloss %	72
 high strength for fast matrix stripping 	brightness (%)	89

print methods: flexographic, offset, letterpress

an aggressive rubber adhesive for wood & horticulture

TimberTack's secret weapon is its surprisingly soft formula. This clever extra aggressive adhesive seeps into every pore and crevice, forming an unbreakable bond with even the roughest, most textured materials. Unlike stiff adhesives that bridge over uneven surfaces, timberTack's soft formula allows it to fill the gaps to create a larger bonding surface for ultimate strength. Nature Lover's Rejoice, timberTack's solvent-free formula is an eco-friendly choice for a wide range of horticultural applications.

extra aggressive moderately soft adhesive high surface contact excellent initial tack high flow properties great cold resistance moderate heat resistance



caliper (+/- 10%) 1.4mil min app temp (°F) 10 service range (°F) -60—145 180° peel (PLI) 5 RT loop tack (PLI) 6 SAFT (°F) 160











This is a 40# bleached, super calendered kraft liner.

This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 2.4mil

total caliper (+/- 10%) 6.6mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

ine