

## Product Data Sheet: C1082

### 50# Coated TT | tire | 50#

Rev. No. 04.01.01 | Date 26DEC24

The 50# Coated TT is a thermal transfer paper coated for flexographic preprinting.

- smooth surface for good bar code reproduction
- smudge resistance for durable bar code image
- high strength for fast matrix stripping
- high brightness and blue-white shade for good label appearance

caliper (+/- 10%)	3.1mil
smoothness (5S, PPS)	2.00
brightness %	85
CD tensile (lbs/in)	17
MD tear (g)	42
opacity %	87

print methods: thermal transfer

facestock

### an aggressive hot-melt adhesive for tires

Tire is a versatile pressure-sensitive adhesive designed to conform to both tire walls and tire tread.

- extra aggressive
- high flow properties
- soft adhesive
- high surface contact
- excellent initial tack / bitey release
- great cold / moderate heat resistance



caliper (+/- 10%)	1.3mil
min app temp (°F)	10
service range (°F)	-60—145
180° peel (PLI)	5
RT loop tack (PLI)	6
SAFT (°F)	160



adhesive

This is a 50# bleached, super calendered kraft liner.  
This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%)	3.1mil
-------------------	--------

total caliper (+/- 10%) 7.5mil

liner

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity  
published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty