

Product Data Sheet: C1099A

2mil Matte Silver PET TC | snappLock A | 50#

Rev. No. 04.01.01 | Date 26DEC24

This face stock is a matte silver polyester with a top coat.
Testing for inks and ribbons is recommended.

high opacity
excellent tear strength
good dimensional stability

caliper (+/- 10%) 2mil
MD/CD tensile (lbs/in) 26k/35k

print methods: flexographic, thermal transfer

facestock

an aggressive hot-melt adhesive for cylindrical applications

SnappLock is a high-performance adhesive boasting exceptional versatility. It has a high initial tack & peel, conquering diverse substrates, including cylindrical applications. Experience increased production efficiency thanks to snappLock's superior die-cutting properties, ensuring consistent, clean cuts.

high performance
superior tack
high surface adhesion versatility
excellent die-cutting
high temperature resistance



caliper (+/- 10%) 0.8mil
min app temp (°F) 40
service range (°F) -40—190
180° peel (PLI) 7.2
RT loop tack (PLI) 11.3
SAFT (°F) 160

adhesive



This is a 50# bleached, super calendered kraft liner.
This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 3.1mil

total caliper (+/- 10%) 5.9mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity
published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

liner