

Product Data Sheet: C1116

3.2mil Matte Wht Synthetic | snappLock | 40#

Rev. No. 04.01.01 | Date 26DEC24

3.2mil Matte Wht PE is a clay-coated two side, highly cavitated & filled, simultaneous biaxial orientated HDPE film.

* to prevent pickers curl, remove the liner from the label

| | | |
|--|------------------------------|---------|
| • superior tear resistance | caliper (+/- 10%) | 3.2mil |
| • great performance with exposure to grease, moisture, and temperature fluctuation | opacity (%) | 90 |
| • easy to die-cut and fold | gloss (%) | 11 |
| • compatible with hot stamping & embossing | MD/CD elongation (%) | 125/130 |
| • up to 18 month outdoor durability | MD/CD tear strength (lbs/in) | 570/650 |
| | stiffness (mg) | 35 |

print methods: thermal transfer, flexographic, gravure, UV offset

an aggressive hot-melt adhesive for cylindrical applications

SnappLock is a high-performance adhesive boasting exceptional versatility. It has a high initial tack & peel, conquering diverse substrates, including cylindrical applications. Experience increased production efficiency thanks to snappLock's superior die-cutting properties, ensuring consistent, clean cuts.

high performance
superior tack
high surface adhesion versatility
excellent die-cutting
high temperature resistance



| | |
|--------------------|---------|
| caliper (+/- 10%) | 1.2mil |
| min app temp (°F) | 40 |
| service range (°F) | -40—190 |
| 180° peel (PLI) | 7.2 |
| RT loop tack (PLI) | 11.3 |
| SAFT (°F) | 160 |



This is a 40# bleached, super calendered kraft liner.
This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 2.4mil

total caliper (+/- 10%) 6.8mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity
estimated roll weight may vary substantially: width (in) x length (in) x 0.0324

published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

facestock

adhesive

liner