

Product Data Sheet: C1126

Direct Thermal TC | frzBite | 40#

Rev. No. 04.01.01 | Date 22OCT24

The Direct Thermal TC is a topcoated, medium sensitivity, direct thermal paper designed for use in standard speed printers.

- print speeds up to 8ips
- good chemical and environmental resistance
- scuff resistant
- high bar code scan rates
- suitable for rotated bar codes
- 190 sensitivity

caliper (+/- 10%)	3.1mil
brightness %	77
MD/CD tensile (lbs/in)	35 / 17
MD/CD tear strength (g)	45 / 45

print methods: direct thermal

facestock

an aggressive hot-melt rubber adhesive for cold temperature

Looking for an adhesive that can withstand the cold? Then you need frzBite! FrzBite aggressive adhesive is designed to perform well in cold temperature environments, making it perfect for food packaging applications. With its superior condensation resistance, frzBite is the ideal choice for any project where reliability in low temperatures is key.

- high cold resistance
- performance through condensation
- low application temperature
- high surface versatility



caliper (+/- 10%)	1.4mil
min app temp (°F)	-10
service range (°F)	-40—140
180° peel (PLI)	5.9
RT loop tack (PLI)	5.6
SAFT (°F)	150

adhesive



This is a 40# bleached, super calendered kraft liner.
This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 2.4mil

total caliper (+/- 10%) 6.9mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity
published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

liner