

Product Data Sheet: C1196

2.6mil Gloss Wht PP TC | snappLock | 40#

Rev. No. 04.01.01 | Date 22OCT24

C1196 features a white, high gloss, BOPP film that is top-coated for excellent print performance and ink adhesion.

excellent die-cut performance
pearlized look for graphics enhancement
great stiffness for efficient dispensability

caliper (+/- 10%)	2.6mil
gloss (45°)	90
opacity %	90
MD/CD elongation %	150/50
MD/CD tensile (k lbs/in)	13.1/29

print methods: UV flexo, water flexo, gravure, UV inkjet, hot stamp, thermal transfer

facestock

an aggressive hot-melt rubber adhesive for cylindrical applications

SnappLock is a high-performance adhesive boasting exceptional versatility. It has a high initial tack & peel, conquering diverse substrates, including cylindrical applications. Experience increased production efficiency thanks to snappLock's superior die-cutting properties, ensuring consistent, clean cuts.

high performance
superior tack
high surface adhesion versatility
excellent die-cutting
high temperature resistance



caliper (+/- 10%)	1mil
min app temp (°F)	40
service range (°F)	-40—190
180° peel (PLI)	7.2
RT loop tack (PLI)	11.3
SAFT (°F)	160

adhesive



This is a 40# bleached, super calendered kraft liner.
This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%)	2.4mil
-------------------	--------

total caliper (+/- 10%) 6mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity
published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

liner