



# D1002

## 2mil Matte Wht Laser PET | Acrylic E3 | 50#

This is a matte white polyester cavitated film. It features a high temperature resistant top coating and provides excellent compatibility with various printing inks, resin ribbons, monochromatic copier and laser printer toners.

caliper (+/- 10%)	2mil
specific gravity (g/cm <sup>3</sup> )	1.084
gloss (60°)	12.8
MD tensile (kg/mm <sup>2</sup> )	12.8
elongation %	113

facestock

EP-3 adhesive is a general purpose acrylic adhesive engineered to have optical clarity, UV resistance, low temperature adhesion, and water/humidity resistance in many general purpose film applications. It provides a high initial tack to most high and medium surface energy substrates, along with high shear strength for low ooze characteristics, providing clean die cutting and matrix stripping.

FDA Compliance:  
Complies with the Code of Federal Regulations,  
Title 21, Section 175.1054  
Solution pH: 7.0+, Neutral Slightly Basic  
Chemical Resistance:  
Acids and Alkalis- Good  
Oils: Excellent

caliper (+/- 10%)	0.8mil
min application temp (°F)	25
service range (°F)	-40—300
180° peel (PLI)	4.2
RT loop tack (PLI)	1.6
shear (hours)	>30

adhesive

This is a 50# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%)	3.1mil
-------------------	--------

liner

total caliper (+/- 10%) 5.9mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty