



Product Data Sheet: D1008 3.25mil Wht Vinyl TC | E-Tire | 50#

Rev. No. 04.01.01 | Date 30APR24

Face Stock

This is a vinyl film with a semi-gloss top coat. special inks are required and testing is recommended

high durability caliper (+/- 10%): 3.25mil
 moisture resistant elongation % (MD/CD): 65-210

- good chemical resistance /120-300

• TC impedes plasticizer migration Tensile Strength (psi, MD/CD): 2800-4500

/ 2500-4000

print methods: offset, flexographic

Adhesive

E-Tire is an aggressive permanent emulsion rubber adhesive.

high tack caliper (+/- 10%): 2mil
 high shear min application temp (°F): 45
 adherance to LSE (low surface energy) service temp range (°F): -20 – 160
 chemical resistance loop tack (oz/in sq): 126

 exceeds most OEM battery label specs for wet cell batteries

Liner

This is a 50# bleached, super calendered kraft liner.

This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%): 3.2mil

total caliper (+/- 10%): 8.45mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity
estimated roll weight may vary substantially: width (in) x length (in) x 0.0324
published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty