



# D1077

## 2mil Wht PET TC | Acrylic Perm | 50#

This white polyester film has a glossy high performance print receptive topcoat. This film provides excellent tear strength, heat resistance, dimensional stability, opacity, and chemical resistance. The high performance print surface is designed to enhance printability with a variety of printing processes- including flexographic and thermal transfer printing.

facestock

caliper (+/- 10%) 2mil  
MD/CD tensile (kpsi) 21/26

Acrylic Perm is a general purpose emulsion acrylic adhesive. It exhibits excellent die cutting and converting characteristics. Acrylic Perm is an excellent choice for cylindrical applications and tight diameter labeling.

adhesive

### Common Applications

- ✦ glass
- ✦ plastics
- ✦ steel

caliper (+/- 10%) 0.7mil  
min application temp (°F) 35  
service range (°F) -40—205  
stainless steel 90° peel (oz) 28  
RT loop tack (oz) 32

This is a 50# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

liner

caliper (+/- 10%) 3.1mil

total caliper (+/- 10%) 5.8mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty