

## Product Data Sheet: C1301

### 3.2mil Matte Wht PP TT | foamLoch | 50#

Rev. No. 04.02.01 | Date 03FEB25

The 3.2mil Matte Wht PP TT is a matte white mineral-reinforced polypropylene film. It is designed for applications requiring strength and durability.

- great strength and durability
- chemical and moisture resistance
- superior printability
- excellent label and card stock

caliper (+/- 10%)	3.2mil
opacity (%)	88
gloss at 60° (GU)	3
MD/CD tensile strength (PSI)	4100/2580
MD/CD tear strength (g/mm)	490/600
MD/CD elongation at break (%)	530/86

print methods: thermal transfer, flexographic, UV inkjet

facestock

### an aggressive hot-melt adhesive for foam

FoamLoch is a highly conformable, high flow aggressive adhesive. This allows for ultra surface contact making this adhesive a great choice for rough, uneven, and porous surfaces- predominately on open cell structure foams.. FoamLoch is perfect for both high-density, firm foam applications as well as low-density, soft foam applications.

- very high flow properties
- ultra soft adhesive
- maximum surface contact
- good initial tack
- excellent cold resistance
- minor heat resistance



caliper (+/- 10%)	2mil
min app temp (°F)	0
service range (°F)	-60—130
180° peel (PLI)	7.5
RT loop tack (PLI)	5.5
SAFT (°F)	140

minimum temperature and service temperature range are projections based off ongoing testing



adhesive

This is a 50# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 3.1mil

total caliper (+/- 10%) 8.3mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

liner