

## label constructions that stick to hing

## Product Data Sheet: C1196-1.2

## 2.6mil Gloss Wht PP TC | snappLock | 1.2mil Clr PET

Rev. No. 04.01.01 | Date 20MAR25

C1196 features a white, high gloss, BOPP film that is top-coated for excellent print performance and ink adhesion.

caliper (+/- 10%) 2.6mil gloss (45°) 90 opacity % 90 MD/CD elongation % 150/50 MD/CD tensile (k lbs/in) 13.1/29

excellent die-cut performance pearlized look for graphics enhancement great stiffness for efficient dispensability

print methods: UV flexo, water flexo, gravure, UV inkjet, hot stamp, thermal transfer

## an aggressive hot-melt rubber adhesive for cylindrical applications

SnappLock is a high-performance adhesive boasting exceptional versatility. It has a high initial tack & peel, conquering diverse substrates, including cylindrical applications. Experience increased production efficiency thanks to snappLock's superior die-cutting properties, ensuring consistent, clean cuts.

high performance superior tack high surface adhesion versatility excellent die-cutting high temperature resistance



caliper (+/- 10%) 1mil min app temp (°F) 40 service range (°F) -40—190 180° peel (PLI) 7.2 RT loop tack (PLI) 11.3 SAFT (°F) 160



















The 1.2mil Clr PET is a clear polyester liner offering enhanced strength and stability for high-speed converting and precision die-cutting.

caliper (+/- 10%) 1.2mil

total caliper (+/- 10%) 4.8mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty