

## Product Data Sheet: D1008

### 3.25mil Wht Vinyl TC | E-Tire | 50#

Rev. No. 04.01.02 | Date 31MAR25

### Face Stock

This is a vinyl film with a semi-gloss top coat.  
special inks are required and testing is recommended

- high durability
- moisture resistant
- good chemical resistance
- TC impedes plasticizer migration

caliper (+/- 10%):	3.25mil
elongation % (MD/CD):	65-210 / 120-300
Tensile Strength (psi, MD/CD):	2800-4500 / 2500-4000

print methods: offset, flexographic

### Adhesive

E-Tire is an aggressive permanent emulsion rubber adhesive.

- high tack
- high shear
- adherence to LSE (low surface energy)
- chemical resistance
- exceeds most OEM battery label specs  
for wet cell batteries

caliper (+/- 10%):	2mil
min application temp (°F):	45
service temp range (°F):	-20 – 160
loop tack (oz/in sq):	126

### Liner

This is a 50# bleached, super calendered kraft liner.  
This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%):	3.2mil
--------------------	--------

total caliper (+/- 10%): 8.45mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity  
published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty